

STUCCO SL20

Technical Sheet

NAME:

STUCCO SL20

TYPE:

Stucco acting as a filler for indoor

USE

To use for grout lines between tiles or in case of cracks or holes, before applying METEORE 12.

TECHNICAL DATA:

specific weight: 1.530 ± 30 gr/LT. at 25°C

viscosity: 35.000 cps

yield: = = =

aesthetic effect: = = =

colours: white

packaging: LT. 0,250-0,500

on the surface: = = =

overpainting 4 hours at 20 °c

below the surface: = = =

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

high toxtropy for filling the joints among tiles and surface leveling

PREPARATION OF THE SURFACE:

PREPARATION OF THE PRODUCT:

dilution: ready to use

system: spatula

number of coatings: 1

APPLICATION:

For grout lines between tiles or in case of cracks or holes, use the STUCCO SL20 filler before applying METEORE 12.

temperature of application superior to + 5°C and inferior to +30°C
storage: make sure that the can is tightly closed, even after use, and store at a temperature between +10°C and +30°C.

stability: approximately 1 year, if the containers are well sealed and never opened

NOTE:

Mix carefully before use. Wash tools using water and soap after use with ethyl alcohol

**Technical Sheet n° SC 00270 issued by the Control Quality Department:
Edition n°2 May 2019**