



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it • www.valpaintjungle.it

SC 00251

ADDITIVO HOLLYWOOD

Technical Sheet:

NAME:

ADDITIVO HOLLYWOOD

TYPE:

Water-based fluorescent additive

USE:

To be added to decorative paints,

CHARACTERISTICS:

specific weight: 1.150 ± 30 gr/LT. at 20°C

viscosity: 550 cps

yield: LT. 0,100 per LT. 1

LT. 0,250 per LT. 2,5

aesthetic effect: Fluorescent to the natural light and to Wood light (neon light or violet light lamp)

colours: colour from the catalogues

packaging: 0,100 lt- 0,250 lt.

DRYING TIME:

on the surface:

overpainting :

below the painting:

CHARACTERISTICS AND RESISTANCE:

The product is stable to light and resistance to washing. Additivo Hollywood is to be poured directly into Arteco'7, Primer 400, Klondike, Klondike Light, Sabulador, Sabulador Soft and Valsetin. Mix carefully before application.

PREPARATION OF THE PRODUCT:

dilution: ready to use- mix well

catalization relation: = = =

pot life: = = =

APPLICATION:

system : add the Additive into the overstated decorative paints and mix carefully before application

number of coating: 1 or more

Storage make sure the tin is tightly closed, even after use, and stored at a temperature no lower than +10°C and no higher than +30°C

Stability: approximately 2 years, if well sealed and never opened

NOTES:

- Working tools must be washed carefully soon after use with water
- Storage and application temperature must be superior to +5°C and inferior +30°C.

Technical Sheet n° SC 00251 issued by the Control Responsible of Quality
Edition n° 2 July 2015