



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.
www.valpaint.it E-mail: info@valpaint.it

SC 00086

FINISH V 15

Technical sheet

NAME:

FINISH V 15

TYPE:

transpiring natural paint for exterior

USE

Natural waxes –based transparent protection for exterior. Formulated and tested to protect Arteco'1 and Arteco'9 and Klondike outside.

TECHNICAL DATA:

specific weight : 850 ± 30 gr/LT. at 25°C

viscosity: = = =

yield: 10 - 15 m²/LT. (it may vary according to the roughness, porosity and surface absorption and to the method of application)

aspect: satined

colours: transparent

packaging: LT. 1

on the surface: 2 hours at 20°C

below the surface: 24 hours at 20°C

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

If it is applied on Arteco'1, Arteco'9 or Klondike outside, it protects the decorative paint from the rain and from UV rays. It avoids colouring fading and lime efflorescent in Arteco'. Wall transpiration on the basis of DIN Rule 52615 (detaching and support-sticking resistance DIN ISO 4624=1,45N/mm²)

= = =

PREPARATION OF THE SURFACE

PREPARATION OF THE PRODUCT:

thinning: ready to use

catalization relation: = = =

pot life: = = =

APPLICATION:

system: use a brush in a circular way as Arteco' application. Do not press strongly the brush as Arteco' paint could be stripped of.

coats: 1 – 2 (it tends to get shiny with two coats)

NOTE:

Keep the product away from cold. Do not apply at temperature inferior to + 5°C.

Technical Sheet n° SC 00086 issued by the Control Quality Department

Edition n° 6

December 2009