



ISO 9001:2008 ED ISO 14001:2004
CERTIFICATO Nr. 501005957 Rev. 02
CERTIFICATO Nr. 501008826

VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v. • E-mail: info@valpaint.it
www.valpaint.it • www.valpaintjungle.it

SC 00179

SETOMAT

Technical Sheet

<u>NAME:</u>	SETOMAT
<u>TYPE:</u>	water-based additive
<u>USE</u>	additive to add to VALSETIN
<u>CHARACTERISTICS:</u>	specific weight: 2.000 ± 30 gr/LT. at 20°C viscosity: = = = yield: LT. 0,100 per LT. 1 of VALSETIN LT. 0,400 per LT. 4 of VALSETIN aesthetic effect: = = = colours: = = = packaging: LT. 0,100 - LT. 0,400
<u>DRYING:</u>	on the surface: = = = over painting: = = = in depth: = = =
<u>CHARACTERISTICS AND RESISTANCE:</u>	water-based additive to add to VALSETIN to get the particular Wallpaper Silk Effect and the Flowered Silk Effect as stated in VALSETIN catalogue.
<u>PRODUCT PREPARATION:</u>	= = = dilution: ready to use; add to VALSETIN mixing carefully. catalisation relation: = = = pot life: = = =
<u>APPLICATION:</u>	system : Add a package of LT. 0,400 of SETOMAT, to LT. 4 of VALSETIN already coloured, or pour LT. 0,100 of SETOMAT in one package of LT. 1 of VALSETIN. number of coatings: = = =

NOTE: The temperature of application and of stocking must not be inferior to +5°C and superior to +30°C. It is suggested to keep away from the sun and from the frost. Tools must be cleaned soon after use with water and soap.

Technical Sheet n° SC 00179 issued by the Control Quality Department

Edition n° 2

April 2005