

## MAGIC LIGHT ADDITIVO S 90

### Technical Scheet

**NAME:**

**MAGIC LIGHT ADDITIVO S 90**

**TYPE:**

Water –based luminescent additive

**USE:**

To be added to decorative paints, transparent waterbased resins, breathable and washable finishes.

**CHARACTERISTICS:**

**specific weight :**

1.460 ± 30 gr/LT at 25°C

**viscosity:**

== =

**yield:**

LT. 0,100 for LT 1.

LT 0,250 for LT 2,51

LT. 0,250 for 5 LT of Sabula 2 or Millicolor Eco

**aesthetic effect:**

Luminescent in darkness

**colours:**

Blue-green in darkness

**packaging:**

LT. 0,100- LT. 0,250

**DRYING:**

**on the surface:**

**Over-painting:**

**below the surface:**

**CHARACTERISTICS AND RESISTENCE:**

MAGIC LIGHT Additive S90 should be added directly to Artecò 7, Klondike, Klondike Light, Sabulador, Sabulador Soft, Valrenna, Velidor Fine, transparent water-based resins, transparent paints and washable finishes; it should be mixed thoroughly before applying it as a final coat. Use paints containing only small quantities of colourings, titanium and covering carbonates, which may reduce the luminous power of MAGIC LIGHT Additive S90 in the dark. N.B.:for Millicolor Eco, Polistof and Sabula 2, namely decorative paints to be applied using a spray, MAGIC LIGHT Additive S90 should be added to even the first coat of the product.

**PREPARATION OF THE PRODUCT:**

**thinning:**

Ready to use – mix well

**APPLICATION:**

**system:**

Pour the additive directly inside the overstated paints and mix carefully before application After the addition of MAGIC LIGHT Additive S90, the product must be applied within 24 hours so that none of its stability is lost

**number coating:**

1 or more

**Application temperature:** between +10°C and +30°C.

**Storage:** make sure that the can is tightly closed, even after use, and store at a temperature between +5°C and +30°C.

**Stability:** approximately 1 year, if the containers are well sealed and never opened

**NOTES:**

Finally, we recommend using MAGIC LIGHT Additive S90 on lighter shades (e.g. C - D - E of the VALPAIN catalogues); darker shades (e.g. A - B) will produce less of a luminescent effect.

When the MAGIC LIGHT additive is used, the SABULA 2 and Millicolor Eco shades will seem slightly lighter.

Tools must be carefully washed soon after use with water

Technical sheet n° SC 00244 issued by the Control Quality Manager:

Edition n° 3

October 2018