

## WATER FREE TRASPARENTE (Transparent)

**NAME:**

**TYPE:**

**USE:**

**TECHNICAL DATA:**

**WATER FREE TRASPARENTE (TRANSPARENT)**

transparent solvent based fixative and consolidating agent

transparent based fixative and consolidating agent for indoor and outdoor

**specific weight:** 960 ± 30 gr/LT. at 20°C (ISO 2811-1)

**yield:** 28 - 30 m<sup>2</sup>/LT. for a coating application by brush  
(it may vary according to the roughness, surface absorption and application methods)

**colours:** transparent

**packaging:** LT. 1, LT. 5

**on the surface:** 8 hours at 20°C

**over painting:** 16 hours at 20°C

**below the surface:** 48 hours at 20°C

**DRYING TIME:**

**CHARACTERISTICS AND RESISTANCE:**

Transparent Water Free is a solvent-based product that can be used as a consolidator on cement, plaster, plasterboard, wood, PVC and light alloys and for chalking or dusty surfaces, as long as they are well cleaned and anchored to the surface; it can also be used as a consolidating finish where a high degree of penetration is to be achieved. The Transparent Water Free must be diluted with 100% synthetic nitro thinner.

**PREPARATION OF THE PRODUCT:**

**thinning:** 100% with white spirit or synthetic diluent

**APPLICATION:**

**catalization relation:** = = =

**pot life:** = = =

**sistem:** brush - roller - spray gun

**coats:** 1-2

**NOTE:**

The storage and application temperature must be between + 5 ° C and + 35 ° C.

Wash tools immediately after use with water and soap with white spirit or synthetic diluent

**Technical Sheet n° SC 00308 issued by the Quality Control Dpt.:**

**Edition n° 2 May 2022**