

SABULADOR EXTERIOR

PRODUCT SPECIFICATIONS

Supply and application of decorative coating with a characteristic sand effect for outdoor and interior surfaces, which produces a highly sophisticated textured finish.

- SABULADOR EXTERIOR MATT FINE (Fine-grain matte)
- SABULADOR EXTERIOR MATT MEDIO (Medium-grain matte)

Old walls or surfaces with a lime base or alkaline pH: Remove any old, loose or flaking paint. Then, wash with water and a suitable detergent. Plaster any surfaces to be painted. Once dry, sand the surface and apply WATER FREE TRASPARENTE diluted 1 to 1 with synthetic thinner or turpentine. After 16 hours at 20°C, apply PRIMER 1400, tinted and diluted to 15-20% with water. PRIMER 1400 should be applied with a PV 09 Brush or a PV 95 Roller in one or two coats to fully cover the surface. Wait 6-8 hours at 20°C before applying SABULADOR EXTERIOR.

New walls: Carefully plaster any surfaces to be painted. When the surface is dry, sand and then apply FISSATIVO ACRILICO 30 G TRASPARENTE, diluted 1 to 5 with water, using a brush or roller. After 8 hours at 20°C, apply PRIMER 1400, tinted and diluted to 15-20% with water. PRIMER 1400 should be applied with a PV 09 Brush or a PV 95 Roller in one or two coats to fully cover the surface. Wait 6-8 hours at 20°C before applying SABULADOR EXTERIOR.

Brush-stroke effect: After carefully preparing the surface according to the instructions, apply a coat of SABULADOR EXTERIOR, using a PV 09 Brush. The technique involves applying plenty of product using short, uniform strokes in all directions.

The technique is to be carried out in accordance with the rules of application, including the materials, application and all the temporary structures necessary for the work.

Cost per square metre € _____