

JUTA

ITEM SPECIFICATION

Supply and application of the JUTA water-based decorative paint for interiors, aesthetically distinguished by a texture reminiscent of the warp and weft of the famous natural fabric, jute. The colour palette offers a range of shades with a matt finish.

The surface to be decorated must be degreased, cleaned and free from any impurities such as: dust, wax, grease, silicone, soap, older layers of paint, and anything else that may prevent adherence. Once dry, sand then use the PV 26 roller to apply two coats of PRIMER 1500 covering the whole surface, creating a thin layer. Wait 4-6 hours at 20°C between the first and second coats of PRIMER 1500. After another 8 hours, proceed with JUTA, again at 20°C.

Use the PV 26 roller for application in a single step, rolling it in all directions but finishing with the final stroke running vertically only, from top to bottom. To spread the product well and achieve the most even decorative result possible, use the roller repeatedly where the "old" and "new" meet so that the two areas, light and dark, blend in.

Immediately afterwards, while the product is wet, pass the special PV 141 or PV 142 roller (patented by VALPAIN) across it in three or more horizontal strokes, followed by another three or more going vertically only.

JUTA is washable to a certain extent, but in order to make the surface even more water-resistant, the FINISH V 10 Opaco transparent protective product must be used after 10 hours at 20°C, to be applied with a roller, a brush, or by spraying.

The work must be carried out in accordance with the specified standards, including the materials, the application, and all the provisional works necessary for the job.

Cost per sqm. € _____