

FINISH V 10

Technical and Environmental Sheet

<u>NAME:</u>	FINISH V 10
<u>TYPE:</u>	breathable varnish for interiors
<u>USE:</u>	matt, transparent protective product for Juta
<u>CHARACTERISTICS:</u>	specific weight: 1,000 ± 30 g/L at 25°C viscosity: = = = coverage: 14-16 m ² /L with one coat (may vary depending on the roughness, porosity and absorption of the surface, and on the method of application) aesthetic effect: matt colours: transparent formats: 0.250 L / 0.500 L surface-dry: 2 hours at 20°C hard-dry: 24 hours at 20°C
<u>DRYING TIMES:</u>	FINISH V 10 is a matt finish designed to protect and preserve the beauty of Juta without altering its natural aesthetic effect. = = =
<u>CHARACTERISTICS AND RESISTANCE:</u>	
<u>PREPARATION OF THE SUPPORT SURFACE:</u>	
<u>PREPARATION OF THE PRODUCT:</u>	dilution: ready to use
<u>APPLICATION:</u>	system: wait 10 hours at 20°C to ensure that the Juta has dried. Then, use a brush, roller or sprayer to apply one or two coats of FINISH V 10 depending on the desired level of washability and resistance. Wait 4 hours at 20°C between the first and second coats. number of coats: 1 - 2 Application temperature: between +10°C and +30°C. Storage: in a tightly closed tin, even after use, at temperatures between +10°C and +30°C. Stability: approx. 1 year in a properly sealed, never-opened container.

NOTES: Mix thoroughly before use. Wash tools immediately after use with soap and water.

Technical Sheet No. SC 00327, issued by the Quality Control Manager:

Edition 1

January 2024

