



VALPAINT S.p.A. Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY Tel. +39 071 906383 (r.a.) - Fax +39 071 906384 E-mail: info@valpaint.it C.F./P.IVA/R.I. di AN 01108220425 Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00035

## FISSATIVO ACRILICO 30 G

## **Technical and Environmental DataSheet**

FISSATIVO ACRILICO 30 G NAME:

TYPE: fixative for plasters, fiber cement, conglomerates

**USE:** it makes uniform the absorption of very porous supports improving the final

painting film making it well anchored to the treated support

**TECHNICAL DATA:** specific weight:  $1010 \pm 30$  gr/lt at 25°C (ISO 2811-1)

viscosity

yield: 20 - 24 m<sup>2</sup>/LT on the product already diluted

(it may vary according to the roughness, surface absorption and

application methods)

aesthetic aspect: === colours: white packaging: 1-4- lt.

**DRYING TIME:** on the surface: 2 hours at 20°C

8 hours at 20°C overpainting 12 hours at 20 ° C below the surface

**CHARACTERISTICS** AND RESISTANCE:

consolidating plaster. Isolates and absorbs absorption, maximizes the yield and application productivity of the finishing product. Overpainted with any type of water-based paint.

**ENVIROMENTAL PERFORMANCES** 

PERFORMANCES	STANDARD	VALUE	BRAND
ABSENCE OF DANGEROUS SUBSTANCES	-	FREE	IPA APEO FORMALDEIDE AMMONIACA FREE
FORMALDEHYDE ISSUE RATE , X	JIS A 1902-3	X< 0.005 mg/m <sup>2</sup> h F****	FORMALDEIDE FREE
VOC On product to use	Directive 2004-42-CE	max 15 g/L (Ue Limit 30 g/L) A/h Cat.	Voc

PREPARATION OF THE

**SURFACE:** 

PREPARATION OF THE dilution

**PRODUCT:** 

**APPLICATION:** system:

plaster and sand

Water 5 parts brush, roll or spray coats:

**Application temperature**: superior to  $+5^{\circ}$ C and inferior to  $+30^{\circ}$ C. Do not apply in direct sunlight or in windy conditions. Avoid days with high humidity or freezing surfaces.

Fissativo Acrilico 30 G

Storage: make sure the can is tightly closed, even after use, at a temperature no lower than  $+ 5^{\circ}$ C and no higher than  $+ 30^{\circ}$ C.

1 parts





VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 [r.a.] - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00035

**Stability:** approximately 2 years in well sealed and never opened can.

**NOTE:** 

Mix carefully the product before use. Wash the tools soon after use with water and soap.

Technical Sheet n. SC 00035 issued by the Control Quality Dpt. :

Edition n. 6 September 2022